

Product Selector

Performance	GT70S Reflex I	GT70S Reflex I+
Weather Performance (BS EN 12207)	■	■
Security to PAS 24:2016	■	■
Uw (Double Glazing with warm edge spacer)*	1.5 W/m²K	1.4 W/m²K
Uw (Triple Glazing with warm edge spacer)**	1.2 W/m²K	1.1 W/m²K
Special Features		
BRE Green Guide Rating ^o	A	A
Design Features		
Dual Colour Option	■	■
Composite Windows	■	■
Ribbon Windows	■	■
Punched Out Openings	■	■
Triple Glazing	■+	■+
Infills:	upto 64mm	upto 64mm
Standard Hardware Groove	■	■
Multi-Point / Single Sided Locking Options	■	■
100mm Restriction	■	■
Trickle Ventilation	■	■
Locking Handles	■	■
System Depth		
72mm	■	■
Maximum Window Sizes[•]		
Tiltturn [•]	1550mm(W) & 2200mm(H)	1550mm(W) & 2200mm(H)
Tiltturn (Side Hung) [•]	1550mm(W) & 2400mm(H)	1550mm(W) & 2400mm(H)
Tiltturn (Bottom Hung) [•]	2400mm(W) & 1200mm(H)	2400mm(W) & 1200mm(H)
Applications		
New Build	■	■
Refurbishment	■	■

Notes:

* Window Energy Ratings and U-values based on CEN size inward opening (1230mm x 1480mm) using 1.0 W/m²K double glazing with warm edge (0.036 W/m²K) spacer.

** U-values based on CEN size inward opening (1230mm x 1480mm) using 0.6 W/m²K triple glazing with warm edge (0.036 W/m²K) spacer.

+ Optional/Limited

• Height and Width Limitations vary dependant on glass weights and hardware requirements – please check with the Technical Services Department

o Corresponds to the BRE Global Green Guide online generic specification for windows and achieves a summary rating of A for non-domestic schemes. www.thegreenguide.org.uk Element Number 1231500007